

DL 14K LOW-PROFILE DUMP PRO

STANDARD CONFIGURATION SPECS
THESE ARE THE DEFAULT SPECS THAT ARE INCLUDED IN THE BASE CONFIGURATION OF THIS MODEL.

 INSIDE BED WIDTH: 83"	 DECK HEIGHT: 28" (24" OPTIONAL)	 CARGO CAPACITY: 7.2 YD³ (UP TO 16.4 YD³)	 Dump Angle: 40°
 LENGTH: 12', 14', 16'	 COUPLERS: Bumper Pull, Gooseneck & Pintle	 AXLES: Tandem (2 x 7,000 lb. or 8,000 lb.) or Triple (3 x 7,000 lbs.)	 Choose the optional 7,000 lb. Electric Drop Axles for an ultra-low 24" bed height.
 GVWR: 14,000 - 21,000 lbs.	 LOAD CAPACITY: 10,400 - 16,750 lbs.	 DUMP SIDES HEIGHT: 24" (with optional 24" side extensions available)	



With its sturdy construction and reliable performance, the Seamless I-Beam creates a more robust and dependable frame, ensuring that your dump trailer can handle even the most demanding jobs.

SEAMLESS I-BEAM FRAME DESIGN



Our UniWall Steel Technology uses form-rolled steel to add structural integrity, reduce corrosion-vulnerable seams, and lower the trailer weight to increase load capacity.

UNIWALL STEEL TECHNOLOGY



The Monster-Sized Toolbox holds the battery and hydraulic pump while also providing an ample amount of storage space for tools, straps, and chains. Plus, it's lockable and features a heavy-duty latch.

MONSTER-SIZED TOOLBOX



Power Up/Power Down & Gravity Down Hydraulic System with Scissor Lift provides efficient lifting capabilities, a stable lifting platform and power-up/power-down functionality for more dump cycles per day.

SCISSOR LIFT WITH POWERFUL CYLINDER

PJTRAILERS