

TH 83" HYDRAULIC QUICK TILT

STANDARD CONFIGURATION SPECS
THESE ARE THE DEFAULT SPECS THAT ARE INCLUDED IN THE BASE CONFIGURATION OF THIS MODEL.

 INSIDE BED WIDTH: 83"	 DECK HEIGHT: 24"	 AXLES: Tandem (2 x 5,200 lbs.)	 Choose the optional Blackwood Pro decking for added durability and grip when wet.
 LENGTH: 18' - 22'	 COUPLERS: Bumper Pull & Pintle	 LOAD CAPACITY: 7,300 - 7,600 lbs.	
 GVWR: 10,000 lbs.	 WEIGHT: 2,400 - 2,700 lbs.	 TILT ANGLE: 10°	



Our front Ram Hydraulic powered system gives you additional stability and control over the precise up and down movement of the bed for additional ease of use and loading/unloading flexibility.

HYDRAULIC POWERED TILT DECK



Simplify brake maintenance with our Forward Self-Adjusting Brakes, engineered to self-adjust for optimal braking performance. This innovative system reduces downtime and ensures consistent stopping power.

FORWARD SELF-ADJUSTING BRAKES



Benefit from enhanced cargo securement with our standard full-length Rubrail and stake pockets. In addition to the built-in stake pockets, the Rubrail provides extra attachment points for securing your load. Customize your trailer further by adding optional D-rings.

CARGO CONTROL STANDARD



Our 30" Diamond plate knife edge tail makes it super-easy to load low clearance equipment like scissor lifts and fork lifts.

KNIFE EDGE TAIL